

Ricochet™ Flexible Wall Protection

Tempo - 17 Colorways

PHYSICAL PROPERTIES

| | |
|--------------|-------------------------------------|
| Width | Trim to 48" |
| Packaging | 15-yd rolls |
| Thickness | 0.033" |
| Backing | Heavy Polyester/ Cotton knit |
| Repeat | N/A |
| Installation | Reverse hang, Random match |
| Fire Safety | Class "A" rated ASTM E-84; NFPA 286 |

ENVIRONMENTAL & HEALTH

| | |
|---------------------|----------------------------------------|
| Indoor Air | Meets California Section 01350 |
| Fungal Resistant | ASTM G-21 |
| Bacterial Resistant | ASTM G-22 |
| HPD | third-party classified |
| EPD | third-party classified |
| NSF/ANSI 342 | third-party certified, ask distributor |

CHEMICAL

| |
|-----------------------------------------------------------------------|
| Chemical Resistance ASTM D-1308, Spot test covered 3.1.1 |
| Cleaning Agents |
| Tide w/H2O |
| Virex |
| Ammonia |
| Isopropyl Alcohol |
| Goof Off |
| Fantastik |
| Lysol |
| Hydrogen Peroxide |
| Bleach |
| Methyl Ethyl Ketone |
| Results: No change in Ricochet surface from exposure to these agents. |

CLEANING

| |
|---------------------------------------------------------------------------------------------|
| Cleaning ASTM F-793, SECTION 7.5 |
| Staining Agents |
| Grape Juice |
| Mustard |
| Black Sharpie |
| Ink Pen |
| Betadine |
| Shoe Polish |
| Lipstick |
| Black Rubber |
| Brake Fluid |
| Spray Paint |
| Results: Each staining agent above was wiped clean with at least one listed cleaning agent. |

ABRASION

| |
|---------------------------------------------------------|
| Abrasion Resistance ASTM D- 4060-14, Taber Method |
| Test Spec |
| CS-10F wheel, 500 gram load @200 cycles |
| Weight loss: 0.02% |

IMPACT

| | |
|-----------------------------------------------------|---------------|
| Impact Resistance ASTM D-5420-10, Gardner Method | |
| Pattern | In-Lbs |
| Tempo | 100+ |

Best stain removal results can be achieved by use of progressively strong, non-abrasive cleaners, and which can be supplemented by use of a soft bristle brush.

OTHER

5-year warranty against manufacturing defects.

Accessories: Coordinating corner guards, top trim and Type II wallcovering (on selected colorways) available.

Installs with techniques similar to Type II vinyl wallcovering, including seaming with overlap and double-cut process.

See full Installation Instructions.

Sold in 15-yd coreless rolls, one per shipping box (approximately 42 lbs)

IPC.3303/REV.1